


Model Name: GA-H77-D3H-MVP 1.1

SHEET TITLE

01	COVER SHEET
02	BOM & PCB MODIFY HISTORY
03	BLOCK DIAGRAM
04	CPU_LGA1155-A
05	CPU_LGA1155-B
06	CPU_LGA1155-C
07	DDR III CHANNEL A
08	DDR III CHANNEL B
09	PCH_FDI,DMI,USB,PCIE,NVRAM
10	PCH_DP,CLK BUFFER
11	PCH_HOST,SATA,PCI
12	PCH_GPIO,CTRL,AUDIO
13	PCH_PWR,GND
14	PCI EXPRESS*16 SLOT
15	PCIEX1*3 , PCIEX4 SLOT
16	ITE8892 PCI BRIDGE
17	PCI SLOT 1&2
18	I/O ITE8728
19	COM, -PROHOT, R_USB
20	Dual BIOS , TPM SLB9635TT
21	VT2021 CODEC
22	REAR AUDIO JACK
23	VCORE PWM_IR3564
24	VCORE PWM DRIVER IR3598
25	NCP3933 OVER VOLTAGE
26	DISCRETE POWER
27	DDR_15V & CPU_VTT PWM IR3570

SHEET TITLE

28	DDR_15V & CPU_VTT PWM DRIVER CHL8550
29	VCCSA POWER
30	F_PANEL , F_USB2.0/3.0
31	ATX POWER, CLOCK GEN
32	HWM , KB/MS , FAN CTRL
33	LAN ATHEROS AR8151
34	N/A
35	M-SATA
36	DVI
37	HDMI , R_USB30
38	TABLE LIST
39	
40	



GA-H77-D3H-MVP

Component value change history

Data	Change Item	Reason
0.1-1124	E-BOM	
02-1216	1. ADD PCH_HS & MOS_HS料號	
	2. PCIE gen2 switch PI3PCIE2415ZHE --> ASM1440	
	3. load-line DAR5=12K , DAR40=1.78K	
10A-0105	1. Z77料號更新	
	2. PWM Driver power vcc or +12V?	
	3. DART2 --> 47K/1/4/S , DAR44 --> 0 ohm	
10B-0113	1. Vcore & VAXG VSEN modify , DAR1,DAR51=100/4/1,DAR2,DAR54=0/4,DAC1,DAC24=3.3nF	
	2. 1.54K加替料:10RC4-001541-22R TA-I	
	1. Remove IR PWM 1X3 pin	
10C-0117	1. DA_DR11,DC_DR11,DZ_DR18 1ohm --> 0ohm	
10D-0119	1. Prochot R65 : 1.65K/4/1 --> 2.74K/4/1	
10E-EVT-0201	1. Modify choke=0.36uH , DRIVER=5V	
10F	1. IR3564要改用新料號03R	
	2. poochot change 100K	
10T	1. 0 OHM Short-pad	
	2. DDR3 FOR OC 2400MHz UP	
10G-1.01	0. PCB Rev1.01 --> Rev1.01 (DDR3 OC 2400MHz+)	
	1. RS_PWM相關線路移除 (若有上prochot pull up改100 ohm)	
	2. Add M/B ID for DDR3 OC	
	3. 固態電容區分100uF/6.3V & 100uF/16V	
10H-1.02	1. PCB Rev1.01 --> Rev1.02 (DDR3 OC 2800MHz+)	
	2. Add M/B ID for DDR3 OC	
	3. ADD DC79 FOR A_CPUPWROK	
	4. 100u 16V-->6.3V	
10I-0430	1. PWM IR3564 --> IR3564A	
	2. Remove DAESD1	
	3. RJK0393DPA 10IF9-040393-01R --> 10IF9-040393-11R	

Circuit or PCB layout change

DATE	Change Item	Reason
P67X-UD3-B3		
2011/02/18-0.1	1. 移除LAR11 ,LAR14 , NR28 ,新增NTP11	
2011/02/18-1.0	2. 新增DR388,DR389,DR391 ; Remove DQ49,DR347,DR371 3. CR44改成R0603-RH 4. R1,LAR3,RBR20,LABC25 -->R0402-2-SHORT 5. RAQ1 --> Q_TO223-MASK 6. RARN1 --> R8P4R-0402-SHORT 7. CESD1-5 --> SSOP5 8. RAQ2,RAEC1一起往下移40mil 9. CESD2文字面要標pin1	
2011/03/8-1.01	1. Add "Dolby" logo	
2011/03/8-1.02	1. UAFB1,UAFB2,UBF1,UBF2 Footprint update 1206-->1812 2. Add "AD1" FOR 5VSB	
Z68XP-D3		
1.0	1. update MINI_PCIE footprint 2. 文字面 : SLOT部分全對齊	
Z77-D3H-0.1	EVT	
0.2-1216	1. Remove SE9172 , Add VCC3 內層(注意其他內層power,跨切割) 2. SPDIF AGND --> GND 3. PCI SLOT & PCIEX1/X4 CAP COST DOWN 4. 0 ohm --> SHORT PAD 5. REMOVE SMBUS FROM COMP TO SOLDER SIDE IN DR POWER 6. SATA3 connect Change to 90 degree (記得SATA3訊號部分要做挖空) 7. Add "108dB"文字面 8. Remove VCC1_05_PCH & VCC1_8_PCH gate net 9. Add EJ168 R_USB30_1 & F_USB3 10. UAE1/UAE2 NET SWAP 11. 內層+12V要打VIA在COMA處 12. SPDIFO_HDMI走12mil	
1.0	1. SATA2-SATA3文字面要隱藏 2. DART2 移至 DC_DQ1左上方 3. Q7 & DAR31 NET Change	
1.01	1. 0 OHM SHORT PAD (LAN & AUDIO) 2. DDR3 2400MHz OC modify (DDR3 DQ 走T型)	
1.02	1. DDR3 2400MHz OC modify (縮小DDR3間距)	
1.1	1. F.B "FB0603-RH" change to "FB0402-RH" 2. ATX_12V_2X2 change to ATX_12V_2X4 3. ACHS105 LAN AR8161 CO-LAYOUT 4. Add pwok R200,BC9 放在ATX 端 5. msATA LAYOUT 龍華& FOXCONN CO-LAY(變更FOOTPRINT) 6. For USB3.0 eTron EJ168A 0.11um modify (UBU1 pin88/89) 7. add VCC1_05_PCH over voltage control	

11A-0703

1. LAN AR8151 --> AR8161

11B-0709

1. EJ168 10HP2-800168-20R --> 10HP2-800168-10R
2. PCIEX16 & PCIEX4 改成雙推式

Gigabyte Technology

BOM & PCB MODIFY HISTORY

Size Custom

Document Number


GA-H77-D3H-MVP


Rev 1.1

Date: Monday, July 09, 2012


Sheet 2 of 38

BLOCK DIAGRAM






Title				DDRIII CHANNEL A			
Size	Document Number			GA-H77-D3H			Rev
Custom							1.
Date:				Sheet 7 of 38			



USB3.0:20/5/7/5/20 (breakout min
8/4/4/4/8) ; ONLY 3 VIAS
Impedance=85 +- 17.5%
Back Panel < 10000 MILS
Front Panel < 6000 MILS




USB2.0 : 12/4.5/7.5/4.5/12 (breakout min 8/4/4/4/8)
Impedance=90 +- 17.5%



放靠近 Device & PCI-E Slot


PCIEX1:16/5/5/5/16 (breakout min 8/4/4/4/8)

Impedance=80 +- 17.5%



FDI:12/4/5/4/12
Impedance=85 +- 17.5%


USB OC#	Configure
OC0#	USB0,1
OC1#	USB2,3
OC2#	USB4,5
OC3#	USB6,7
OC4#	USB8,9
OC5#	USB10,11
OC6#	USB12,13
OC7#	Not Use






NVRAM

Gigabyte Technology


Title			
PCH FDI,DMI,USB ,PCIE			
Size	Document Number	Rev	
Custom	GA-H77-D3H	1.1	
Date:	Monday, July 09, 2012	Sheet	9 of 38





Flex0,2 : 33MHz
Flex1,3 : 27/14/24/48/25MHz



Differential Clock: 18/4/6/4/18
Impedance=90 +- 15%





Check if NC for P67 non graphic chip





Gigabyte Technology			
Title			
PCH DISPLAY ,CLK BUFFER			
Size	Document Number	Rev	
Custom	GA-H77-D3H	1.1	
Date:	Monday, July 09, 2012	Sheet	10 of 38

SATA2 : 15/7.5/4.5/7.5/15 (breakout min 8/4/4/4/8)
Impedance=90 +- 17.5%









+12 protect
short-wire
test

PCIE16:16/5/5/5/16

PA_EXP_RXP0.[15] >> PA_EXP_RXP0.[15] [4]
PA_EXP_RXN0.[15] >> PA_EXP_RXN0.[15] [4]
PA_EXP_TXP0.[15] >> PA_EXP_TXP0.[15] [4]
PA_EXP_TXN0.[15] >> PA_EXP_TXN0.[15] [4]

PA_EXP_TXP0	PAC5	0.22u/4/X5R/6.3V/K	PA_EXP_TXP0 C
PA_EXP_TXN0	PAC4	0.22u/4/X5R/6.3V/K	PA_EXP_TXN0 C
PA_EXP_TXP1	PAC6	0.22u/4/X5R/6.3V/K	PA_EXP_TXP1 C
PA_EXP_TXN1	PAC7	0.22u/4/X5R/6.3V/K	PA_EXP_TXN1 C
PA_EXP_TXP2	PAC8	0.22u/4/X5R/6.3V/K	PA_EXP_TXP2 C
PA_EXP_TXN2	PAC9	0.22u/4/X5R/6.3V/K	PA_EXP_TXN2 C
PA_EXP_TXP3	PAC10	0.22u/4/X5R/6.3V/K	PA_EXP_TXP3 C
PA_EXP_TXN3	PAC11	0.22u/4/X5R/6.3V/K	PA_EXP_TXN3 C
PA_EXP_TXP4	PAC12	0.22u/4/X5R/6.3V/K	PA_EXP_TXP4 C
PA_EXP_TXN4	PAC13	0.22u/4/X5R/6.3V/K	PA_EXP_TXN4 C
PA_EXP_TXP5	PAC14	0.22u/4/X5R/6.3V/K	PA_EXP_TXP5 C
PA_EXP_TXN5	PAC15	0.22u/4/X5R/6.3V/K	PA_EXP_TXN5 C
PA_EXP_TXP6	PAC16	0.22u/4/X5R/6.3V/K	PA_EXP_TXP6 C
PA_EXP_TXN6	PAC17	0.22u/4/X5R/6.3V/K	PA_EXP_TXN6 C
PA_EXP_TXP7	PAC18	0.22u/4/X5R/6.3V/K	PA_EXP_TXP7 C
PA_EXP_TXN7	PAC19	0.22u/4/X5R/6.3V/K	PA_EXP_TXN7 C
PA_EXP_TXP8	PAC20	0.22u/4/X5R/6.3V/K	PA_EXP_TXP8 C
PA_EXP_TXN8	PAC21	0.22u/4/X5R/6.3V/K	PA_EXP_TXN8 C
PA_EXP_TXP9	PAC22	0.22u/4/X5R/6.3V/K	PA_EXP_TXP9 C
PA_EXP_TXN9	PAC23	0.22u/4/X5R/6.3V/K	PA_EXP_TXN9 C
PA_EXP_TXP10	PAC24	0.22u/4/X5R/6.3V/K	PA_EXP_TXP10 C
PA_EXP_TXN10	PAC25	0.22u/4/X5R/6.3V/K	PA_EXP_TXN10 C
PA_EXP_TXP11	PAC26	0.22u/4/X5R/6.3V/K	PA_EXP_TXP11 C
PA_EXP_TXN11	PAC27	0.22u/4/X5R/6.3V/K	PA_EXP_TXN11 C
PA_EXP_TXP12	PAC28	0.22u/4/X5R/6.3V/K	PA_EXP_TXP12 C
PA_EXP_TXN12	PAC29	0.22u/4/X5R/6.3V/K	PA_EXP_TXN12 C
PA_EXP_TXP13	PAC30	0.22u/4/X5R/6.3V/K	PA_EXP_TXP13 C
PA_EXP_TXN13	PAC31	0.22u/4/X5R/6.3V/K	PA_EXP_TXN13 C
PA_EXP_TXP14	PAC32	0.22u/4/X5R/6.3V/K	PA_EXP_TXP14 C
PA_EXP_TXN14	PAC33	0.22u/4/X5R/6.3V/K	PA_EXP_TXN14 C
PA_EXP_TXP15	PAC34	0.22u/4/X5R/6.3V/K	PA_EXP_TXP15 C
PA_EXP_TXN15	PAC35	0.22u/4/X5R/6.3V/K	PA_EXP_TXN15 C

PCI-E REV:1.1--> 2.5GHZ


PCE-E X1(單向) BANDWITH=2.5GHz*(8b/10b)=2Gb/s=250MB/s

PCE-E X1(雙向) BANDWITH=2.5GHz*(8b/10b)X2=4Gb/s=500MB/s

PCE-E X16(單向) BANDWITH=2.5GHz*(8b/10b)X16=32Gb/s=4GB/s

PCE-E X16(雙向) BANDWITH=2.5GHz*(8b/10b)X16X2=64Gb/s=8GB/s

PCI-E REV:2.0--> 5GHZ




PCI-E/16X-164P/297C/LONG DOUBLE


Gigabyte Technology

Title			
PCI EXPRESS * 16			
Size	Document Number	Rev	
Custom	GA-H77-D3H	1.1	
Date:	Monday, July 09, 2012	Sheet	14 of 38


PCIE*4





PCIE*1



PCIE*1



PCIE*1




Function	SEL
X1--> x0a	L ₁ PCIEX4 SLOT-->X1
X1--> x0b	H ₁ PCIEX4 SLOT-->X4


Gigabyte Technology






PCIE X1 1.2

Title	Document Number	Rev
GA-H77-D3H	1.1	1.1
















Date: Monday, July 09, 2012 15 of 38







	IT8721	IT8728
PIN121	FAN_CTL4/VID_TURBO	VCORE_EN/PCH_C0
PIN120	VDDA_EN	VLDT_EN/PCH_D0
PIN19	GP30	ATXPG
PIN31	GP14	PCH_C1
PIN53	SST/AMDTISI_D/PECI_AVA/MTRB#/PCH_D	SST/AMDTISI_D/MTRB#/PCH_D1
PIN55	PECI/AMDTISI_C/DRVB#/PCH_C	PECI/AMDTISI_C/DRVB#
PIN66	GP47	SYS_3VSB
PIN70	SYS_3VSB	GP47
PIN95	VIN3/ATXPG	VIN2(VCC5)
PIN96	VIN2	VIN1(VCC12)
PIN97	VIN1(VCC5)	VIN1/VDIMM_STR(1.5V)
PIN98	VIN0(VCC12)	VIN0/VCORE(1.1V)



Gigabyte Technology			
Title			
ITE 8728 LPC IO			
Size	Document Number	Rev	
B		1.1	
Date:	Monday, July 09, 2012	Sheet	18 of 38

MOSI For DMI RX Termination Voltage

[12] N_ICH_SPI_MOSI >> N_ICH_SPI_MOSI NR10 8.2K/4/X
[12] N_ICH_SPI_CS >> N_ICH_SPI_CS NR9 8.2K/4/X
-SPI_HOLD0 NR3 1K/4/1
-SPI_HOLD1 NR11 1K/4/1

[12] N_-SPI_WP1 >> N_-SPI_WP1 NR2 8.2K/4/X
[12] N_-SPI_WP0 >> N_-SPI_WP0 NR1 8.2K/4/X
[12] N_ICH_SPI_MISO >> N_ICH_SPI_MISO NR5 8.2K/4



[11] N_-GNT0 >> NR26 1K/4/1/X
[11] N_-GNT1 >> NR25 1K/4/1/X

Default int pull up

SPI_MISO NR6 22/4 << N_ICH_SPI_MISO [12]

BOOT DEVICE	GNT0	GNT1
LPC	0	0
PCI	0	1
NAND	1	0
SPI	1	1

1 means floating
0 means PD 1K




Gigabyte Technology



Title	BIOS		
Size	Document Number	GA-H77-D3H	Rev 1.1
Date:	Monday, July 09, 2012	Sheet 20 of 38	

CR36: 20K/4/1 @Realtek cdec & VT1708S-CE
CR36: 5.1K/5/1 @VIN codec VT1708S-CD/VT2021
C3638 100pF @VIN codec VT1708S


100pF/4NPO/50V/JXX

CR36 5.1K/4/1







VCORE Phase 1,3




VCORE Phase 4,2




VAXG Phase




VAXG PHASE 1,2



MOS HEATSINK




CPU_VTT



$$OCP: 46A = \frac{R_{oset} * I_{ocset}}{R_{ds}(on)}$$


$$= \frac{27K * 10uA}{5.9m}$$

CPU_VTT PWR SEQ



GIGABYTE


Title		
RT8120_CPU_VTT		
Size	Document Number	Rev
Custom	GA-H77-D3H	1.1
Date:	Monday, July 09, 2012	Sheet 25 of 38



VIN=5V, VOUT=1.5V, IOUT=25A, PHASE=1
IRMS=11.45A
560u/FP/D/6.3V/68/8m RIPPLE CURRENT=4.7A
Coefficient=1.7(85°C), 1(105°C)
VIN Ripple current=4.7X1.7=7.99A(85°C)
-->故固態電容須2X7.99=15.98>11.45A
OCP : $I_{peak} = (I_{ocset} \times R_{ocset}) / R_{dson}$
typ $I_{ocset}=10\mu A$, $R_{ocset}=33k$
OCP : $37A = (10\mu A \times 11k) / (5.9m / 5.9m)$
OCP : $52A = (10\mu A \times 11k) / (4.2m / 4.2m)$
UVP : 75%*Vout
Fsw = 300KHz


Remote sense請從最重的負載端點拉回
 $0.8 * (1 + RS / RO) = V_{out}$
 $0.8 * [1 + 2K / 2.2K] = 1.527V$

GIGABYTE™			
Title			
RT8120 DDR 15V			
Size	Document Number		Rev
Custm	GA-H77-D3H		1.1
Date:	Monday, July 09, 2012	Sheet	26 of 38




NCT3933	0X2A	0X20	0X22	0X26
VREF1	DDR_VTT	VREF_DDRA_DQ	SMREF	VCORE
VREF2	VREF_DDRA_CA	DDR15V	VCC1_8_PCH	CPU_VTT
VREF3	VREF_DDRA_CA	VREF_DDRB_DQ	VCCSA	VAXG


Gigabyte Technology		
CPU CORE VR-2		
Size	Document Number	Rev
Custom	GA-H77-D3H	1.1
Date:	Monday, July 09, 2012	Sheet 27 of 38













PCH ErP Control




VCC_SA






ATX POWER CONNECTOR




CLK GEN



CPU Frequency Selection


FS	CPU
0	100M <Default>
1	133M




Gigabyte Technology

Title		
ATX POWER CONNECTOR		
Size	Document Number	Rev
Custom	GA-H77-D3H	1.1
Date:	Monday, July 09, 2012	Sheet 31 of 38


TEMP H/W MONITOR




VOLTAGE-- H/W MONITOR




KB/USB




CPU SMART FAN



SYS FAN_2 +12V





SYS FAN_3



SYS FAN_1

Linear SYS_FAN



Gigabyte Technology

HWM,KB/MS, FAN CTRL


Size	Document Number
Custom	GA-H77-D3H

Date: Monday, July 09, 2012


Sheet 32 of 38

Rev
1.1

LAN:AR8151/AR8161



USB30_LAN CONNECTOR




LAN POWER


NEW DESIGN ONLY FOR INTERNAL SWR







AR8151: LAR3(O), LAR5(X)

AR8161: LAR5(O), LAR3/LAR4(X)



MDI : AR8161-->N/A





Max Power=2.2V x 0.15A=0.33Watt


AZ1117H-1.2TR/SOT223/1A-->UR17:0/4,UR16:N/A [1.2V]


L1117LG/N/SOT223/1A-->UR17:0/4,UR16:100/4/1 [1.25V]

USB3.0 --> 5GHz

BANDWITH=5GHz*(8b/10b)=4Gb/s=500MB/s

GIGABYTE™		
Title		
E-TRON EJ168		
Size	Document Number	Rev
Custom	GA-H77-D3H	1.1
Date:	Monday, July 09, 2012	Sheet 34 of 38






HDMI:20/4/6/4/20


Impedance=85 +- 17.5%

HU1




0/0/0/0:Vswing 500mV

0 1:7.2dB



USB30_20



R_USB30_2

USB18P/BU/OS/RA/D/2/HR

USB3.0/2.0

VBUS

D-

D+

GND

SSRX+

SSRX-

GND

SSTX+

SSTX-

AGND

AGND

AGND

AGND

AGND

AGND

AGND

AGND

AGND

AGND

AGND

AGND

AGND

AGND

AGND

AGND

AGND

AGND

AGND

AGND

AGND

AGND

AGND

AGND

AGND

AGND

AGND

AGND

AGND

AGND

AGND

AGND

AGND

GIGABYTE™


Title			
HDMI & USB			
Size	Document Number		Rev
Custom	GA-H77-D3H		1.1
Date:	Monday, July 09, 2012	Sheet	37 of 38

PCH GPIO LIST TABLE					
PIN NAME	PWR	Default	USAGE	NOTE	
GP0	MAIN	H-Z	GPI0	N/A	
GP1/TACH1	MAIN		GPI01	N/A	
GP2/PIRQE#	MAIN		GPI	-PIRQE	P/U 8.2K VCC3
GP3/PIRQF#	MAIN		GPI	-PIRQF	P/U 8.2K VCC3
GP4/PIRQG#	MAIN		GPI	-PIRQG	P/U 8.2K VCC3
GP5/PIRQH#	MAIN		GPI	-PIRQH	P/U 8.2K VCC3
GP6/TACH2	MAIN		GPI	PCIEX1 Detect	P/U 8.2K VCC3
GP7/TACH3	MAIN		GPI	GPI07	P/U 8.2K VCC3
GP8	STBY	H	GPI	GPI08	N/A
GP9/OC5#	STBY		NATIVE	USB OC5#	N/A
GP10/OC6#	STBY		NATIVE	USB OC6#	N/A
GP11/SMBALERT#	STBY		NATIVE	USB PWR protect	P/U 8.2K 3VDUAL
GP12	STBY	L	GPI	GPI012	N/A
GP13	STBY	L	GPI	LPCPME#	P/U 8.2K 3VDUAL
GP14/OC7#	STBY		NATIVE	USB OC7#	N/A
GP15	STBY	L	GPI	GPI015(TLS Enable)	P/U 8.2K 3VDUAL
GP16	MAIN		GPI	GPI016	P/U 8.2K VCC3
GP17/TACH0	MAIN		GPI	GPI017	P/U 8.2K VCC3
GP18	MAIN		GPI	Mobile Only	N/A
GP19	MAIN		GPI	GPI019	P/U 8.2K VCC3
GP20	MAIN		GPI	GPI020	P/U 8.2K VCC3
GP21	MAIN		GPI	GPI021	P/U 8.2K VCC3
GP22	MAIN	H-Z	GPI	GPI022	P/U 8.2K VCC3
GP23	MAIN		GPI	GPI023	N/A
GP24	STBY	L	GPI	SKTOCC#	N/A
GP25	STBY			Mobile Only	N/A
GP26	STBY			Mobile Only	N/A
GP27	STBY	H	GPO	GPI027	P/U 8.2K 3VDUAL
GP28	STBY	H	GPO	PWR LED	P/U 8.2K 3VDUAL
GP29	STBY	L	GPI	GPI029	N/A
GP30	STBY	H-Z	GPI	Mobile Only	N/A
GP31	STBY	H-Z	GPI	Mobile Only	N/A
GP32	MAIN	H	GPO	N/A	N/A
GP33	MAIN	H	GPO	N/A	N/A
GP34	MAIN	H-Z	GPI	-PCI_STOP	P/U 8.2K VCC3
GP35	MAIN	L	GPO	-ACZ_DET	P/U 8.2K VCC3
GP36	MAIN		GPI	N/A	N/A
GP37	MAIN		GPI	N/A	N/A
GP38	MAIN	H-Z	GPI	PCIEX4 Detect	P/U 8.2K VCC3
GP39	MAIN	H-Z	GPI	GPI039	P/U 8.2K VCC3
GP40	STBY		NATIVE	USB OC1#	N/A
GP41	STBY		NATIVE	USB OC2#	N/A
GP42	STBY		NATIVE	USB OC3#	N/A
GP43	STBY		NATIVE	USB OC4#	N/A
GP44	STBY	L	NATIVE	GPI044	P/U 8.2K 3VDUAL
GP45	STBY		NATIVE	GPI045	P/U 8.2K 3VDUAL
GP46	STBY	L	NATIVE	GPI046	P/U 8.2K 3VDUAL
GP47	STBY			Mobile Only	N/A
GP48	MAIN	H-Z	IN	GPI048	P/U 8.2K 3VDUAL
GP49	MAIN	H-Z	IN	GPI049	P/U 8.2K 3VDUAL
GP50	MAIN		NATIVE	-REQ1	P/U 2.2K VCC
GP51	MAIN	H	NATIVE	-GNT1	N/A
GP52	MAIN		NATIVE	-REQ2	P/U 2.2K VCC
GP53	MAIN	H	NATIVE	-GNT2	N/A
GP54	MAIN		NATIVE	-REQ3	P/U 2.2K VCC
GP55	MAIN	H	NATIVE	-GNT3	N/A
GP56	STBY		NATIVE	Mobile Only	N/A
GP57	STBY	H-Z	IN	VCORE_OV1	P/U 8.2K 3VDUAL
GP58	STBY	H-Z	NATIVE	F_USB_OC	P/U 8.2K 3VDUAL
GP59	STBY		NATIVE	USB_OC0#	N/A
GP60	STBY	H-Z	NATIVE	N/A(Reverse)	P/U 8.2K 3VDUAL
GP61	STBY	L	NATIVE	-SUSTAT	N/A
GP62	STBY	L	NATIVE	SUSCLK	N/A
GP63	STBY	L	NATIVE	GPI063	N/A
GP64	MAIN	L	NATIVE	CLKOUTFLEX0	N/A
GP65	MAIN	L	NATIVE	CLKOUTFLEX1	N/A
GP66	MAIN	L	NATIVE	CLKOUTFLEX2	N/A
GP67	MAIN	L	NATIVE	CLKOUTFLEX3	N/A
GP72	STBY	H-Z	NATIVE	VCORE_OV4	P/U 8.2K 3VDUAL
GP73	STBY			Mobile Only	N/A
GP74	STBY	H-Z	NATIVE	1_05V_OV2	P/U 8.2K 3VDUAL
GP75	STBY	H-Z	NATIVE	N/A(Reverse)	P/U 8.2K 3VDUAL


Super I/O ITE8720 GPIO Table

PIN NAME	USAGE	NOTE
SVC/PECI_RQT/GP14	-PECI_REQ	
PWROK1/GP13	PWROK1/ITE_PWROK	
KRST#/GP62	-KBRST	
SO/GP50	-ICH_SPI_CS	
IRTX/GP47/CE2_N/JP7	CEB_N	
GP46/IRRX	-LAN2_DSM	
PSION#/GP42	-PSON	
PWROK2#/GP41	PECI_CTL	
PCIRST3#/GP10/VDIMM_STR_EN	-PCIE_RST	
RSMRST#CIRRX1/GP55	-RSMRST	
PME#/GP54	-LPCPME	
PD5/GP75/BUSS00	N/A	

PIN NAME	USAGE	NOTE
FAN_TAC2/GP52	FANIO2	
FAN_TAC3/GP37	FANIO3	
VIDO3/FAN_TAC4/GP25/DSR2#	FANIO4	
FAN_CTL2/GP51	FANPWM2	
FAN_CTL3/GP36	FANPWM3	
VID4/GP34	BEEP-	
VID3/GP33	TURBO1	
VID2/GP32	TURBO0	
VCORE_GOOD/VID6/GP63	CPUT_LED1_C	
VID5/GP35	CPUT_LED2_C	
VID1/GP31	CPUT_LED3_C	
VID0/GP30	-LAN1_DSM	NBT_LED1_C
SLCT/GP80	CPU_LED1_C	
PE/GP81	CPU_LED2_C	
BUSY/GP82	CPU_LED3_C	
PD3/GP73/BUSS11	SB_LED1_C	
PD4/GP74/BUSS12	SB_LED2_C	
VCORE_EN/VID7/GP64	IT_GP64	SB_LED3_C
PD0/GP70	NB_LED1_C	
PD1/GP71	NB_LED2_C	
PD2/GP72/BUSS10	NB_LED3_C	
GP22/SCK	LOW_PWR_1	
VID05/GP27/SIN2	LOW_PWR_2	
PCIRST2#/GP11	-PFMRST1	
PCIRST1#/GP12	-PFMRST2	
3VBSBW#/GP40	CSI_F0	BSEL166_1
SUSC#/GP53	CSI_F1	BSEL166_2
GP23/SI	BSEL166_3/CSISBSL	
VID00/GP20/CTS2#	CPUT_LED1_C	BSEL166_4
GP65/VDDA_EN/GB_01	MB_ID2	
PD6/GP76/BUSS01	MB_ID3	
PD7/GP77/BUSS02	MB_ID4	
AFD#/GP86/SMB_C_R	2X_PIN	FST_2X8
INIT#/GP85/SMB_D_M	SRC_2x8	GTLREF_AD2
ACK#/GP83	DDR_LED1_C	
VID01/GP21/DCD2#	DDR_LED2_C	
STB#/GP87/SMB_C_M	DDR_LED3_C	
PWRON#GP44	VCORE_OV1	
PANSWH#/GP43	PWRBTSW	
KDAT/GP61	-PWRBTSW	
KCLK/GP60	KDAT	
MDAT/GP57	KCLK	
MACL/GP56	MDAT	
GP66/VLDT_EN/GB_02	NBT_LED1_C	MCLK
SVD/PCIRSTIN#/CIRTX/GP15	PWM2_CR	
KDAT/GP61	PWM2_CR	
GP67/CPU_PG/GB_03	EN_LOADLINE	IT_GP67/-EN_PWM2
SLIN#/GP84/SMB_D_R	-EN_PWM2	
PSI_L/FAN_CLT5/CIRRX2/GP16	-THERM	
VID04/GP26/SCOUT2	DDR18V_PH2_EN	
VID02/FAN_TAC5/GP24/DSR2#	DDR18V_LED	
VID06/GP17/RI2#	1_1V_PH_EN	
VID07/JP6/DTR2#	JP6	
PD5/GP75/BUSS00	SB_LED3_C	



PWM各相位的擺法如下：



BIOS超電壓對應表：

線路圖名稱	BIOS選項
Vcore	CPU Vcore
CPU_VTT	CPU Termination
CPU_VAXG	CPU Graphic Core
VCC1_8_PCH	CPU PLL
VCC1_05_PCH	PCH core
3VDUAL	3VDUAL
DDR15V	DRAM voltage
DDRVTT	DRAM Terminatio
VREF_CA_A/VREF_CA_B	DRAM Address Ref
VREF_DQ_A/VREF_DQ_B	DRAM Data Ref

散熱模組料號：

Z77-D3H :
PCH :
12SP2-S05511-01R/02R/03R
MOSFET :
12SP2-S08924-01R/02R/03R

	3 pin FAN control	4 pin FAN control	FAN speed	Controller
CPU FAN	FANPWM1	FANPWM3	FANIO1	IT8720
	ICH_FAN_PWM2	ICH_FAN_PWM0	ICH_FAN_TACH0	PCH
SYS FAN	FANPWM2	N/A	FANIO2	IT8720
	ICH_FAN_PWM1	N/A	ICH_FAN_TACH1	PCH
PWR FAN	N/A	N/A	FANIO3	IT8720
			ICH_FAN_TACH2	PCH

Gigabyte Technology			
File	TABLE LIST		
Size	Document Number	GA-H77-D3H	
C			Rev 1.1
Date	Monday, July 09, 2012	Sheet	38 of 38