



C325/C225 Brazos BLOCK DIAGRAM




Voltage Rails


Power	Voltage	S0	S3	S4	S5	G1	On Signal
VCCRTC	3V	ON	ON	ON	ON	ON	Adaptor IN
VIN	20V	ON	ON	ON	ON	OFF	Adaptor IN
5V_AUX	5V	ON	ON	ON	ON	OFF	Adaptor IN
2V_AUX	3.3V	ON	ON	ON	ON/OFF	OFF	Adaptor IN
3V_S5	3.3V	ON	ON	OFF	OFF	OFF	S5_ON15V
1.1V_S5	1.1V	ON	ON	OFF	OFF	OFF	S5_ON15V
5V_S3	5V	ON	ON	OFF	OFF	OFF	MAINON_10V15
3V_S3	3.3V	ON	ON	OFF	OFF	OFF	MAINON_10V15
1.5V_S3	1.5V	ON	ON	OFF	OFF	OFF	MAINON_10V15
1.1V_S3	1.1V	ON	ON	OFF	OFF	OFF	MAINON_10V15
5V	5V	ON	OFF	OFF	OFF	OFF	MAINON_10
3V	3.3V	ON	OFF	OFF	OFF	OFF	MAINON_10
1.8V	1.8V	ON	OFF	OFF	OFF	OFF	MAINON_10
1.5V	1.5V	ON	OFF	OFF	OFF	OFF	MAINON_20
1.2V	1.2V	ON	OFF	OFF	OFF	OFF	MAINON_20
1.1V	1.1V	ON	OFF	OFF	OFF	OFF	MAINON_20
1V	1.05V	ON	OFF	OFF	OFF	OFF	MAINON_20
BIOSD_VFORM	0.75V	ON	OFF	OFF	OFF	OFF	BIOSD
CPU_CORE		ON	OFF	OFF	OFF	OFF	VRON
NB_CORE		ON	OFF	OFF	OFF	OFF	VRON
VGA_CORE	1.8V	ON	OFF	OFF	OFF	OFF	MAINON_2
1.8_VGA	1.8V	ON	OFF	OFF	OFF	OFF	MAINON_20P15
1.5_VGA	1.5V	ON	OFF	OFF	OFF	OFF	MAINON_20P15
1.0_VGA	1V	ON	OFF	OFF	OFF	OFF	MAINON_20P15

When RTC wake up and S5 WOL Function enable, 3V_S5 will turn on in S5 mode.




QUC Power On/Off Sequencing Timing Diagram











```
External CPU Thermal sensor delete
Brazos on-die thermal sensor support.
```



www.aitech1.ru









CLEAR CMOS JUMPER.

SATA trace should use only 1via on the trace.
customers can use 2vias with GND via within 150mils of
signal via as long as they can ensure that their platform
meets SATA logo requirements. Return loss is expected
to get affected with 2 vias. AMD platforms are validated
with one via only

ODD

HDD



4Mbyte

Q20

Q21

Q22

Q23

Q24

Q25

Q26

Q27

Q28

Q29

Q30

Q31

Q32

Q33

Q34

Q35

Q36

Q37

Q38

Q39

Q40

Q41

Q42

Q43

Q44

Q45

Q46

Q47

Q48

Q49

Q50

Q51

Q52

Q53

Q54

Q55

Q56

Q57

Q58

Q59

Q60

Q61

Q62

Q63

Q64

Q65

Q66

Q67

Q68

Q69

Q70

Q71

Q72

Q73

Q74

Q75

Q76

Q77

Q78

Q79

Q80

Q81

Q82

Q83

Q84

Q85

Q86

Q87

Q88

Q89

Q90

Q91

Q92

Q93

Q94

Q95

Q96

Q97

Q98

Q99

Q100

Q101

Q102

Q103

Q104

Q105

Q106

Q107

Q108

Q109

Q110

Q111

Q112

Q113

Q114

Q115

Q116

Q117

Q118

Q119

Q120

Q121

Q122

Q123

Q124

Q125

Q126

Q127

Q128

Q129

Q130

Q131

Q132

Q133

Q134

Q135

Q136

Q137

Q138

Q139

Q140

Q141

Q142

Q143

Q144

Q145

Q146

Q147

Q148

Q149

Q150

Q151

Q152

Q153

Q154

Q155

Q156

Q157

Q158

Q159

Q160

Q161

Q162

Q163

Q164

Q165

Q166

Q167

Q168

Q169

Q170

Q171

Q172

Q173

Q174

Q175

Q176

Q177

Q178

Q179

Q180

Q181

Q182

Q183

Q184

Q185

Q186

Q187

Q188

Q189

Q190

Q191

Q192

Q193

Q194

Q195

Q196

Q197

Q198

Q199

Q200

Q201

Q202

Q203

Q204

Q205

Q206

Q207

Q208

Q209

Q210

Q211

Q212

Q213

Q214

Q215

Q216

Q217

Q218

Q219

Q220

Q221

Q222

Q223

Q224

Q225

Q226

Q227

Q228

Q229

Q230

Q231

Q232

Q233

Q234

Q235

Q236

Q237

Q238

Q239

Q240

Q241

Q242

Q243

Q244

Q245

Q246

Q247

Q248

Q249

Q250

Q251

Q252

Q253

Q254

Q255

Q256

Q257

Q258

Q259

Q260

Q261

Q262

Q263

Q264

Q265

Q266

Q267

Q268

Q269

Q270

Q271

Q272

Q273

Q274

Q275

Q276

Q277

Q278

Q279

Q280

Q281

Q282

Q283

Q284

Q285

Q286

Q287

Q288

Q289

Q290

Q291

Q292

Q293

Q294

Q295

Q296

Q297

Q298

Q299

Q300

Q301

Q302

Q303

Q304

Q305

Q306

Q307

Q308

Q309

Q310

Q311

Q312

Q313

Q314

Q315

Q316

Q317

Q318

Q319

Q320

Q321

Q322

Q323

Q324

Q325

Q326

Q327

Q328

Q329

Q330

Q331

Q332

Q333

Q334

Q335

Q336

Q337

Q338







Q339

Q340


Q341


Q342

Q343



DELETE TEST VIA






REQUIRED STRAPS



OVERLAP COMMON PADS WHERE POSSIBLE FOR DUAL-OP RESISTORS.


11



	ACZ_SDOUT	PCI_CLK1	PCI_CLK2	PCI_CLK3	PCI_CLK4	INT_EC_EN	INT_CLK_EN	ROMTYPE_1/0
PULL HIGH	LOW POWER MODE	ALLOW PCIE Gen2 DEFAULT	Watchdog Timer Enable DEFAULT	USE DEBUG STRAPS	non_Fusion CLOCK MODE	INTERNAL EC ENABLED	INT. CLKGEN ENABLED DEFAULT	H, H=Reserved H, L=SPI ROM DEFAULT
PULL LOW	PERFORMANCE MODE DEFAULT	FORCE PCIE Gen1	Watchdog Timer Disable	IGNORE DEBUG STRAPS DEFAULT	Fusion CLOCK MODE DEFAULT	INTERNAL EC DISABLED DEFAULT	EXT. CLKGEN ENABLE	L,H=LPC ROM L, L=FWH ROM

internal have pull Hi 10x

DEBUG STRAPS



	PCI_AD27	PCI_AD26	PCI_AD25	PCI_AD24	PCI_AD23
PULL HIGH	USE PCI PLL DEFAULT	DISABLE ILA AUTORUN DEFAULT	USE FC PLL DEFAULT	DISABLE I2C ROM DEFAULT	DISABLE PCI MEM BOOT DEFAULT
PULL LOW	BYPASS PCI PLL	ENABLE ILA AUTORUN	BYPASS FC PLL	ENABLE I2C ROM use REQ3# as SDA use GNT3# as SCL	ENABLE PCI MEM BOOT



Quanta Computer Inc.


PROJECT : QUD(C225)

Size Document Number Rev A


STRAPS/PWRGD


Date: Wednesday, May 18, 2011 Sheet 11 of 37


CHANNEL A DIMM 1 H5.2



CHANNEL A DIMM 0 H9.2









CNTRL1	CNTRL0	V-CORE
1	1	0.85V
1	0	0.9 V
0	1	1.0 V
0	0	1.1 V


ALLOW FOR PULLUP PADS FOR THESE STRAPS AND IF THESE GPIOs ARE USED, THEY MUST NOT CONFLICT DURING RESET		
STRAPS	Name	DESCRIPTION OF DEFAULT SETTINGS
TX_PWRS_ENB	GPIO0	Transmitter Power Savings Enable 0: 2.5% Tx output swing for mobile mode 1: full Tx output swing (Default setting for Desktop)
TX_DEEMPH_EN	GPIO1	PCI Express Transmitter De-emphasis Enable 0: Tx de-emphasis disabled for mobile mode 1: Tx de-emphasis enabled (Default setting for Desktop)
BIF_GEN2_EN_A	GPIO2	0: Advertises the PCIe device as 2.5 Gb/s capable at power-on. 1: Advertises the PCIe device as 5.0 Gb/s capable at power-on. Note: 5.0 Gb/s capability will be controlled by software.
BIF_VGA_DIS	GPIO9	VGA Disable determines whether or not the card will be recognized as the system's VGA controller. 1: VGA Controller capacity enabled 0: The device will not be recognized as the system's VGA controller
BIOS_ROM_EN	GPIO22	ENABLE EXTERNAL BIOS ROM 1:enable 0:disable
ROMCFG2(2:6)	GPIO[13:11]	Primary Memory Aperture size requested Size of the primary memory apertures CONFIG2(2:6) 128 MB 000 256 MB 001 512 MB 010 1 GB 011 Note: For frame buffers larger than 256 MB (e.g. 512 MB, 1 GB) the aperture size should be 256 MB.
VIP_DEVICE_STRAP_ENA	DAC2_VSY	IGNORE VIP DEVICE STRAPS 1:enable 0:disable
AUD[1] AUD[0]	EXT_CRT_HS_VSYNC EXT_CRT_VSYNC	AUD[1] AUD[0] 0: 0 No audio function 0: 1 Audio for DisplayPort and HDMI if dongle is detected 1: 0 Audio for DisplayPort only 1: 1 Audio for both DisplayPort and HDMI
RSVD RSVD RSVD	GPIO0, GPIO_21_BB_EN GENCLK_CLK	Internal use only. Internal use only. Internal use only.










DDR3 BGA MEMORY

19

















4 IN 1 CARD READER




Share Pin

Share Pin	XD	MS	SD
SP1	XD0/BS#		SD_D7
SP2	XD_RS#		SD_D6
SP3	XD_CS#		SD_D5
SP4	XD_WE#		SD_D4
SP5	XD_CLE	MS_BS	
SP6	XD_ALE	MS_D5	
SP7	XD_WP	MS_D1	
SP8	XD_D0	MS_D4	
SP9	XD_D1	MS_D0	
SP10	XD_D2	MS_D2	
SP11	XD_D3	MS_D6	
SP12	XD_D4	MS_D3	
SP13	XD_D5	MS_D7	
SP14	XD_D6	MS_CLK	
SP15	XD_D7		SD_WP




www.aitech1.ru


www.aitech1.ru



Touch Panel (Define by EETI module)
QUB ONLY




HOLE




WEB CAM MODULE

(Define by Bison CCD module)




POWER SWITCH/LED


FUNCTION BUTTON BOARD




UMA CRT FOR DEBUG

Discrete CRT for Debug










ISL6265 Pin1	OFS	VFIXEN
1.2V	V	X
3.3V	X	V
5V	X	X


VFIXEN VID Codes

SVC	SVD	Output
0	0	1.4
0	1	1.2
1	0	1.0
1	1	0.8










TDC:6.5A
OCP=12A
f=400kHz
IL=2.3A

ESR=16mohm
V=2.3*16=37mV


OCP
=Current limit + Iripple/2
=(5.1K*10uA/4.7mohm) + (2.3A/2)=12A




Quanta Computer Inc.


PROJECT : QCU (C205)


Size	Document Number	Rev
	VCC1.0(RT8202A)	4D
Date:	Wednesday, May 18, 2011	Sheet 32 of 37




www.aitech1.ru









www.aitech1.ru

1.Reserve U22,U23,C400,C365-For debug use.
2.Reserve R19 and Mount R18-Enable HDMI function.
3.Reserve/short R289,R290,R297,R302,R6.
4.D5 power source change to 3.3V_LDO
5.Reserve/Short R184,R160,R337,R398,R321,R117,R389.
6.Delete L8 and Change 3.3V_TV power source to 3.3V
7.Add C3170,C3171,Y5,R808,R809,R8011,R8012,R8013.
8.Delete Q8 and CDD_Power_on# net
9.Reserve C5,C4.
10.Delete R434,R426,R423,R422,R415.
11.Delete LED1-LED6, Q9-Q13, R304-R309 for debug use.
12. Change C242 power source to 5V_S3.
13.Delete L7,C243,C225.
14. Change CN20 pin1 power to 5V_S3, pin 2 to VCC5 and delete pin8 CIR_RX0 net.
15.Add F10,F11 for safety concern.
16.Change C140,C226 footprint.
17. Del R172 not mount
18. Del R275 not mount
19. R7 from 150 ohm change to 499 ohm
20. MB_HDMI_DDCCLK change link to CN15[B18]
21. MB_HDMI_DDCDATA change link to CN15[B19]
22. Change CN7 footprint
23. Change J1 footprint
24. Change CN14 footprint
25. Change CN16 footprint
26. Change CN11,CN17 footprint
27. Change CON1, CON2 footprint

power 3/22
28.change PC87 to SMT type
29.PC138,PC184,PC116,PC149,PC134,PC190change to 2200PF
30.PK70 change to 0402 type
31.PR171,PR166 mount 2.2 ohm,PC151 1500PF
32.add PC19(1500pf)
33.add PC163(0.22uf)
33.PR135 change to 150K
34.PR116 change to 115K
35.FU7 pull low 47K.
36.delete PC100
37.PQ4,PQ40 change to FDS6690AS
38. PR19 change to 120K
39.PC96 change to 0603 type
40.FU7 pin6 change net to 3V_AUX
41.PR71 pull high change to 3V_S3
42.PC179 change to 0603 type
43.PC6,PC92,PC38,PC35,PC75,PC30 change to 0603 type

3/25 update
44. Add D26,D27,D28,D29 diodes
45. Change U18 AZ1015-048
46. CN18 add Pin 22, 23 link to GND
47. Change AR29 to 100K ohm
48. Change power net from AVDD to VREG5
49. Change Q6,Q7 add Q5523, Q5524 2N7002
50. LV_HDD add C675,C676 for EMI
51. 5V add C677,C678 for EMI
52. CN14 change link [2]SATA_RXP1_C
53. CN14 change link [3]SATA_RXN1_C
54. CN14 change link [5]SATA_TXN1_C
55. CN14 change link [6]SATA_TXP1_C
3/28 update
56. Del APU_VADJ_2130S net, R288, R64,SW1, R69, R91 for Adj/WB
57. Del R8218, R79, FCH_14318M_CR net use external crystal for Scalar
58. Short pad R101
59. Reserve R433,
60. Change C226,C140 to 330U/6.3V_R6_17 SMD type
61. Change H1 footprint to hg-c276d138p2
62. Change R462 footprint to short0603.
63. Add R536, R537, R538, R539 reserved resister for EMI
64. Remove DDR window component. (C25, C26, C55, C33, C34)
65. Del H15 for DXF
3/29 udate
66. D26,D27,D28,D29 change to 1S8355
67. Change R8011,R8012,R8013 to 75ohm
68. AR27 change to 100k ohm
69. Add CIR_RX0 net
70. CN21 change footprint for layout vicky
71.Add AR51 1K ohm for decerase currect when power on.
72.Add R8014,R8015 and Q5525 for HDMI hot plug detect for Discrete SKU.
3/30 update
73. H13 change footprint
4/1
74. CN14 change link [2]SATA_TXP1_C
75. CN14 change link [3]SATA_TXN1_C
76. CN14 change link [5]SATA_RXN1_C
77. CN14 change link [6]SATA_RXP1_C
4/17
78. Change power net name FU9[3], PR187[1]from 3V_AUX to 3.3V_AUX
79. Modify DDR page need to mount the parts
4/27
80. Del USB_OC function, D28,R235,R236,PR108, USB_OC7#_R
81. Del USB_OC function, D29,R131,R132,PR182, USB_OC4#_R
82. Del USB_OC function, C673,F2,D26, R225,R220, PR181 USB_OC5#_R
83. Del USB_OC function, C674,F1,D27, R224,R219, PR183 USB_OC6#_R

5/08 update
84. Reserve DMICinterface R1,R2,C2,C3
85. R184 footprint change to Short0402
86. OSD_ON# add 4.7K ohm R810 pull up to 3.3V
87. EC Pin 69 2270_FUN1# move to EC pin 16
88. EC Pin 70 2270_FUN2# move to EC pin 120
89. EC Pin 71 2270_FUN3# move to EC pin 115
90. EC_PHYSICS (R490)and EC_WHITE(R487)3.3V_LDO power change to 3.3V
91. Reserve CON3
92. Reserve R480 WL_EN Pull up resister
93. WLAN change power from 3.3V change to 3V_S5
94. Add audio bias voltage AR65.AR66,AR67,AR68,AR69, AR70,AC49,AC50

5/11 update Jeff
84. PR166 chang to 0805 type
85. PL14 change PN which vendor TTY
86. PC87 change to 330uf and add PC197
87. PQ22,PQ25,PQ39,PQ49,PQ57 change PN
88. Delete PR164,PR167,PR174,PR145,PR168,PR169,PR172,PR198,PR191,PR79,PR91
5/11 Anson
89. CN9 Pin1 lin to PCIE_WAKE#
90. R435 change to 3V_S5
91. R432 change to 3V_S5
92. R536,R537,R538,R539 change to 150 ohm
93. R6 remove to BOM(short pad)
94. EC pin 73 link to R811,R812

R0C-->R0D
6/09
95. Del U8 TC7SH08FU
96. Add fuse at HDD/ODD 5V power for 3C test
97. Modify NUT P/N to MBQU1002010 for H9, H14 location
98. Add U34,U35 EEPROM Co-lay

power 6/15

99. PC127 change to 330p
100. PC126 change to 0.022uf
101. PC125 change to 8200pf
6/17
102. CN7 change footprint to sata-ld1107f-s33t5-7p-r

www.aitech1.ru