




Intel Apollo Platform Block Diagram




PCB 6L STACK UP


LAYER 1 : TOP
LAYER 2 : VCC
LAYER 3 : IN1
LAYER 4 : IN2
LAYER 5 : GND
LAYER 6 : BOT













HARDWARE STRAPS (* = SYSTEM STRAP SELECTION)				
GPIO_39: INTERNAL 20K PD *DISABLE CSE ROM BYPASS: 0 ENABLE CSE ROM BYPASS: 1	GPIO_47: INTERNAL 20K PD *DON'T FORCE DNX FW LOAD: 0 FORCE DNX FW LOAD: 1	GPIO_106: INTERNAL 20K PU *MUST BE HIGH WHEN RSM_RST_N DEASSERTS	GPIO_117: INTERNAL 20K PD *MUST BE LOW WHEN RSM_RST_N DEASSERTS	GPIO_120: INTERNAL 20K PD *TOP SWAP OVERRIDE DISABLE: 0 TOP SWAP OVERRIDE ENABLE: 1
GPIO_40: INTERNAL 20K PD *MUST BE LOW WHEN RSM_RST_N DEASSERTS	GPIO_48: INTERNAL 20K PD *MUST BE LOW WHEN RSM_RST_N DEASSERTS	GPIO_111: INTERNAL 20K PU DO NOT BOOT FROM SPI: 1 *BOOT FROM SPI: 0	GPIO_123: INTERNAL 20K PU MUST BE HIGH WHEN RSM_RST_N DEASSERTS	GPIO_121: INTERNAL 20K PD *MUST BE LOW WHEN RSM_RST_N DEASSERTS
GPIO_43: INTERNAL 20K PU ENABLE BOOT FROM EMMC: 1 *DISABLE BOOT FROM EMMC: 0	GPIO_104: INTERNAL 20K PD *MUST BE LOW WHEN RSM_RST_N DEASSERTS	GPIO_118: INTERNAL 20K PD *NO FLASH DESCRIPTOR OVERRIDE: 0 OVERLAY FLASH DESCRIPTOR: 1	GPIO_112: INTERNAL 20K PD *MUST BE LOW WHEN RSM_RST_N DEASSERTS	
GPIO_44: INTERNAL 20K PU *ENABLE BOOT FROM SPI: 1 DISABLE BOOT FROM SPI: 0	GPIO_105: INTERNAL 20K PD *MUST BE LOW WHEN RSM_RST_N DEASSERTS	GPIO_110: INTERNAL 20K PU LPC BUFFERS AT 1.8V: 1 *LPC BUFFERS AT 3.3V: 0	GPIO_113: INTERNAL 20K PD *MUST BE LOW WHEN RSM_RST_N DEASSERTS	














Quanta Computer Inc.

PROJECT : ZRX


Size	Document Number	Rev
	APL NO CONNECT	1A
Date: Friday, July 21, 2017	Sheet 10 of 38	








PCH SPI FLASH





EC SPI FLASH


www.aitech1.ru

DO WE WANT DO USE THE 1.8V LDO?
ADD 1.8V SPI PART











RESET IC




32 GB EMMC SD STORAGE

150 uA SLEEP CURRENT



SD Connetcor


www.aitech1.ru



TAI - SOL

Quanta Computer Inc.	
PROJECT : ZRX	
Size	Document Number
eMMC/SD	Rev 1A

Date: Friday, July 21, 2017




AMBIENT TEMPERATURE SENSOR SHOULD BE PLACED NEAR HEADPHONE JACK, AWAY FROM ICS
DO NOT CHANGE THERMISTOR TYPE

FINGER PRINT CONNECTOR

Not - Ready


Modify the pins assignment to meet Quanta's layout symbol rule.



NFC CONNECTOR

SUBJECT TO CHANGE PER QUANTA REQUEST



Remove This Function




TOUCHPAD BOARD CONN (TPD I2C/PS2 co-lay)

(TPD)

TPD->10KHz, Ts=400Khz
Intel design guide suggestion
Max. Pwr. 10u.
Des. Lndg. 10u.
TS=3x5inch
400Khz10->10u=2.4-0.4K.
100Khz 10->100u=9k-1k.



KB_BL Control




11/3/16
Remove Pen connector
Add KB backlight circuit


Quanta Computer Inc.
PROJECT : ZRX

Size Document Number Rev
BASE: KB, TP, NFC, FINGER 1A
Date: Friday, July 21, 2017 Sheet 20 of 38


EDP2-EDP3 DOES NOT NEED TO ROUTE TO CONNECTOR



CCD/DMIC BOARD (KX022+DMIC)




EDP + TouchScreen Connector



Sensor I2C Level shift


Remove This Function

TOUCH SCREEN




C-PANEL CAMERA

Remove This Function




M.2 connector (Wifi+BT)








www.aitech1.ru


GPS connector

Remove This Function










PORT 0

PROVIDES ESD PROTECTION, PLACE CLOSE TO CONNECTOR

PP5000_A
C307
150u6.3V_3528H1.9

DRIVE 3.3V = EN@3A
EC PU = EN@1.5A
DRIVE 0V = OFF
EC HI-Z = OFF

B2A_Update U38 FP to sot23_213-2_4-95-1_1h



www.aitech1.ru


PORT 1

PROVIDES ESD PROTECTION, PLACE CLOSE TO CONNECTOR

PP5000_A
C308
150u6.3V_3528H1.9


DRIVE 3.3V = EN@3A
EC PU = EN@1.5A
DRIVE 0V = OFF
EC HI-Z = OFF

B2A_Update U39 FP to sot23_213-2_4-95-1_1h




POWER - BATTERY CHARGER


ROHM BUCK-BOOST CHARGER




POWER - PMIC LOGIC




POWER - PMIC RAILS




PP3300_A




PP5000_A





POWER - LOAD SWITCHES






Locate with TPM (Page 21)





Low-speed connector



6/23/16

ADDED 1 MORE PPVAR_USB_C1_VBUS PINS
ADDED 1 MORE PP5000_USB_A1_VBUS PINS
REMOVED 2 GND PINS



8/11/16

ADDED EC_VOLUP_BTN_ODL TO PIN25(17)
ADDED EC_VOLDN_BTN_ODL TO PIN26(16)

8/30/16

ADDED TABLET_MODE TO PIN24

High-speed connector



Model	Version	CHANGE LIST							
ZRX	B	2017/3/7 page 20 Change U18 U19 P/N to SN1702001RTER page 23 Change J6 footprint to ngff-nase0-s6701-tsh4-ke-smt 2017/3/9 page 24 Change R37 from 5.11K ohm to 11.8K ohm for Build 2 page 31 Change R528 to 30Kohm for thermal protect when temp is 76.3C page 20 Change U18 U19 P/N to SLGC55545VTR page 36 Change J18 P/N form DFFC30FR181 to DFFC30FR172							
Ramp	C	2017/4/6 page 29 DNI R20 , Add C4884 0.1uF Cap to GND on CHARGER_IADP_RESET_L page 06 Changed R38 and R39 pull-up value to 1K 2017/4/11 page 24 Add EOSD/ESD solution (R4539 33ohm and C194 180pF) on EC_TPD_EN Change EC_TS_EN from EC_GPIO83 to EC_GPIO00 Add EOSD/ESD solution (R4542 33ohm and C4887 180pF) on LID_OPEN page 21 Change EC_TS_EN from J19 Pin23 to J19 Pin8 , Add EOSD/ESD solution (R4540 33ohm and C4885 180pF) on EC_TS_EN Add EOSD/ESD solution (R4541 33ohm and C4886 180pF) on EDP_HPD_3V3 Add pull High Register(R4543 100k ohm) on TOUCHSCREEN_EN_3V3_OD page 20 Add ESD solution (D41) on MECH_PWR_BTN_IN_ODL page 24 Change R37 to 20.5K (BUILD 3) 2017/4/12 page 24 Add EOSD/ESD solution (R459 2.2ohm and R4544 2.2ohm) on Embed Controller Power (U12.M13/U12.N1 and U12.C13/U12.H13 page 07 change Q79,Q81,Q82 P/N to PJA3413 2017/5/04 page 21 DNI R4543 2017/5/11 page 20 DNI SW3 (Hardware power Key) 2017/5/15 Change 0-ohm to short pad page 04 R12,R13,R14,R15 page 05 R281 page 08 R461,R462,R463,R464 page 14 R77,R78,R79,R80,R84,R85,R86,R87 page 15 R180~R187,R174,R200 page 19 R96,R43,R44,R48,R49,R110,R102,R103,R104,R105,R28,R108,R305,R109 page 20 R4535,R4536,R4537 page 21 R4521,R4524 page 24 R146 page 25 R254,R255 page 29 R328,R330,R400,R406,R524 page 31 R407,R408,R414,R525,R530 page 33 R498 page 35 R813,R818 ~ R823,R826,R827,R828,R841,R842,R847 ~ R853,R855,R856,R334 ~ R338,R450 ~ R452,R503,R504,R873,R874,R876,R859 ~ R866,R869~R872 2017/5/17 Change milli-ohm to short pad page 30 R393/0.51ohm 2017/5/18 DNI INAs Function page 16 Q68,Q69,Q75,C442,C443 page 30 R892,R893 page 31 R882,R883,R884,R885,R886,R887,R890,R891 page 32 R878,R879,R880,R881,R4322,R4323 page 33 R897,R898,R899,R900,R901,R902,R903,R904 Change milli-ohm to short pad page 30 R402/0.02ohm,R403/0.02ohm page 31 R460/0.002,R412/0.01,R416/0.02,R417/0.02,R425/0.002 page 32 R422/0.002,R415/0.51,R421/0.002 page 33 R364/0.02,R367/0.02,R368/0.1,R369/0.1,R370/0.02,R381/0.02,R383/0.02,R384/0.1,R386/0.02,R387/0.1,R389/0.02,R390/0.02 2017/5/24 ADD PMIC Power Issue Debug page 30 Add R4548, R4348 0 ohm resistor and change R393 to 0 ohm. page 31 Add R4350 0 ohm resistor. 2017/6/02 page 25 Change U18,U19 P/N to TI-SN1702001RTER 2017/6/12 page 30 Change the net name at 55 pin of PMIC to PMIC_VSYS. page 31 Add U98 group for PMIC issue in PMIC_VSYS 2017/6/15 page 30 Add R4550 bypass to avoid U41 Logic unit							

Model	Version	CHANGE LIST
ZRX	C Ramp	<p>2017/6/19 page 6 Add R4538 on GP_15 for S3 issue. It can using TP to wake up on S3</p> <p>2017/6/19 Change 0-ohm to short pad page 30 R4548 ,R393 page 33 R385</p> <p>2017/7/28 page 30 DNI J1, R519 ,U44 ; Remove SERVO Function</p>

www.aitech1.ru

